



John Bouchard & Sons

1024 Harrison St, Nashville, TN 37203 | P: 615-256-0112 | F: 615-256-2427

JBS-ACC-32

ROTARY-SCREW COMPRESSOR CLEANER AND SYSTEM FLUSH

Applications:

JBS-ACC-32 is a premium quality synthetic fluid designed to dissolve varnish and solubilize sludge from rotary-screw air compressors during operation. It can also be used as a system flush when changing-over from mineral to synthetic oils in order to reduce contamination due to oil carry-over. Regular use of **JBS-ACC-32** will help you get the most out of your synthetic oil and your compressor by removing varnish and reducing operating temperature.

Typical Industrial Applications:

- Rotary Screw Compressor
- Rotary Vane Compressor
- Centrifugal Compressor

Performance Benefits:

- Solubilizes and removes harmful varnish and “sludge”
- 100% synthetic
- Contains no aromatic solvents or hazardous ingredients
- Contains additives so that it can be used as a lubricant for up to 500 hours
- High flash point
- Caution: May affect some paint finishes, plastics and seals
- USDA H-2 authorized

<u>TYPICAL PROPERTY</u>	<u>TEST METHOD</u>	<u>JBS-ACC-32</u>
ISO Grade	ASTM D2422	32
SAE Grade	SAE J-300	10
Viscosity @ 40°C,cSt	ASTM D445	37.1
Viscosity @ 100°C,cSt	ASTM D445	6.5
Viscosity Index	ASTM D2270	126
Flash Point, °C/°F	ASTM D92	204/400
Pour Point, °C/°F	ASTM D97	-45/-49
Copper Corrosion	ASTM D130	1b
Demulsibility	ASTM D1401	Excellent
Specific Gravity	ASTM D1298	0.94